

PRODUCT INFORMATION

SSL-100 Vertical Sleeve Labeler

Our SSL-100 vertical sleeve labeler is a performance-driven label applicator with a small footprint able to label at up to 100 CPM. You'll find the same construction and touch control interface of our other labeling machines integrated into a small machine with big format options. Sleeve Seal's modular change parts allow for easy adaptation to both round and non-round formats with a tool-less adjustment system that allows fast, easy changeovers.



PRODUCT DESCRIPTION & SPECIFICATIONS

Drive Train

The SSL-100 vertical sleeve labeler drive train is engineered around Allen Bradley controls plus precision machined components that are designed for accuracy and durability. Our drive train design offers repeatable performance in a mechanically simple system that uses modular change parts that make switching between formats easy. All of our mechanical systems can be adjusted by the operator with no tools which gives Sleeve Seal labelers the reputation for being operator friendly, long lasting machines capable of efficiencies of 99.5%. All Sleeve Seal labelers perform precision labeling thanks to well-engineered components managed by Allen Bradley servos and controls.

Access Cabinet

Every Sleeve Seal machine is housed in a heavy gauge stainless steel cabinet and includes lockable service doors for ease of maintenance and safety. Access to the front of the cabinet is managed with Allen Bradley safety interlock switches to ensure safety. Operators are able to manage operation and changeovers using a customized HMI and synchronized adjusters.

Cutter Box

Our patented cutter box design utilizes four to eight synchronized cutting blade heads for fast, precise cuts that won't leave jagged film ends. Sleeve Seal cutter boxes use common, affordable utility blades that can be found in a local hardware store with other blade types available for use in harsh environments. Sleeve Seal's modular design allows for easy replacement of blades and fast changeovers between formats.

SSL-100 Production Rate:	100 CPM
Bottle Sizes:	25 - 128 mm diameter
Label Length:	25 - 250 mm
Label Thickness:	40 - 80 micron (μm)
Materials:	PET, PVC, OPS

